## **Medallion LVT**

## **Technical Data**

Mt. Tam III Luxury Vinyl Plank by Medallion	
Collection Name:	Mt. Tam III Luxury Vinyl Plank by Medallion
Use	Gluedown Residential & Commercial
Size	3mm (1/8") x 7.25" x 48", 20 mil Wearlayer
Material	100% Virgin PVC Vinyl
Thickness	3mm (1/8" Nominal)
Wear Layer	20 mils (0.50 mm). UV-cured Urethane
Embossing	Mechanical pressed embossing
Bevel	Square Edge
Recommended Adhesive	Mapei ECO 399
Planks/Carton	13 pieces
Sq. Ft./Carton	31.46 sq.ft.
Cartons Per Pallet	50 cartons, 1573.16 sq.ft. per pallet
Weight Carton	38 lbs.
Pallets Container	22 Pallets on 40' container, 34,606 sq.ft.
Warranty	Lifetime Residential & 10 year Commercial Limited Wear Warranties
	ASTM Test Results
Test	Results
ASTM E648-2019a Critical Radiant panel	Class 1
ASTM E662-2021a Smoke Density	Class 1
Floor Score &	REACH Certified, 100% Virgin PVC, Phthalate-Free
	Important Notice

Vinyl flooring is sensitive to extreme heat and direct sunlight.

Mantaining an optimum temperature between 55F-85F and humidity range of 30-50% is recommended during installation and life of floor.

To prevent excessive expansion, avoid exposure to direct sunlight for prolong periods of time. During peak sunlight hours, use drapes, blinds, shears or solar film to minimize exposure.

2434 Polvorosa Avenue \* San Leandro, CA 94577 \* Phone 510-351-8104 \* Fax 510-351-7480
839 F Street, Suite 100 \* West Sacramento, CA 95605 \* Phone 916-372-8501 \* Fax 916-372-2175

Hawaii \* Phone 808-836-3585 \* Fax 808-834-4722

www.Medallion1.com