


# U-PLY®

## Premium Plywood Underlayment



**Medallion**

[www.medallion1.com](http://www.medallion1.com)

- Lifetime Warranty (Commercial & Residential)
- For use under all floor coverings
- Score/Snap with a Knife
- Marine grade adhesive
- 5-Ply Dent Resistant Construction
- Guaranteed Against Yellowing and Delamination
- 4'x 8' Sheets Available
- 1/4" Nominal Thickness
- 100% Farmed Sustainable Wood



## INSTALLATION INSTRUCTIONS

Acclimate **U-PLY**<sup>®</sup> panels 24 to 48 hours to the room environment in which they will be installed.

1. Install **U-PLY**<sup>®</sup> printed side down before installing the finished floor.
2. Install the long dimension of the panel perpendicular to the floor joints for maximum rigidity.
3. Offset seams with sub floor seam by at least 6". **U-PLY**<sup>®</sup> scores and snaps with a knife for easy installation.
4. Stagger panels, ashlar fashion so that four corners do not meet. Offset underlayment joints by at least 16".
5. Leave a minimum 1/8" gap at walls.
6. Lightly butt all panels, but don't force sheets into place.
7. Fasten panels securely to a structurally sound, smooth, clean and dry sub-floor with 18 gauge staples with chiseled ends and or 12 gauge non-staining galvanized ring
8. Groove shank nails.
9. Make sure fasteners don't penetrate through the sub-floor into floor joist.
10. Position fasteners in the field on 4" centers.
11. Attach edge fasteners 1 1/2" apart and 3/8" from edge.
12. Set fasteners flush or slightly below the panel surface.
13. **Option 1:** Fill all edge joints and other service depressions with a Portland Based Latex Modified Patch and hand sand smooth. No belt sander needed, as we have pre sanded **U-PLY**<sup>®</sup>. Make sure patch is FULLY DRY before installing the finished floor. **Option 2:** Do not use patch at all, just make certain all panels are lightly butted together.



## DISCLAIMER

Woodstock Supplies has the highest standards of quality in the marketplace. Environment and temperature should be noted to ensure proper acclimation. Flooring should be installed immediately after underlayment installation to prevent site-influenced damage. Woodstock Supplies is not responsible for faulty installation. No defective material is to be installed. Final inspection of each panel is the responsibility of the installer.

## LIFETIME WARRANTY 100% JOB REPLACEMENT

**U-PLY® Premium Underlayment** will hold all floor coverings firmly when the floor covering is installed in accordance with the floor covering and adhesive manufacturer's instructions. **U-PLY®** is guaranteed for life in all applications when product is handled and used as floor underlayment in accordance with these installation instructions.

- Not to delaminate
- Not to be the sole cause of "yellowing"
- Not to transfer wood colors to the floor covering

Under this warranty any and all implied warranties are expressly limited to, at the company's option: *Refunding the full cost (including installation cost) of the underlayment, adhesive and floor covering affected.*

In the event of yellowing an independent lab will be employed to determine the cause of the yellowing, the "at fault" material supplier will be liable for all costs incurred due to the problem. In no event shall the company's liability for any claim exceed the wholesale cost (*including installation cost*) of the underlayment, adhesives, and floor covering affected.

This warranty does not cover damages due to improper installation of floor covering material. In addition, tears or rupture to the floor surface, tile pop, standing water, fire, floods, natural disasters or faults in the plumbing which affects the performance of the flooring system are not covered. This warranty is transferable and covers all commercial and residential applications. Liability shall expressly exclude any other liability to the purchaser or any other person for direct, indirect or consequential damages.

You must notify **WOODSTOCK SUPPLIES** within 30 days after discovery of product found to be defective under this warranty. An authorized representative from Woodstock Supplies must be given the opportunity for 30 days after such notice to inspect floor prior to any alterations, change or repair. In any case where Woodstock Supplies is not notified before any alterations, change or repair is made to the floor, Woodstock Supplies is released from any liability on the claims.

**All claims must be submitted in writing within 30 days after the discovery of any defect. Please email to [cathyn@woodstocksupplies.com](mailto:cathyn@woodstocksupplies.com).**

