

PROJECT PLUS BY MEDALLION
12 mil Wearlayer - Gluedown LVP Plank

	<i>Plank</i>
<i>Use</i>	<i>Residential & Commercial</i>
<i>Wearlayer</i>	<i>12 mils (.30 mm) UV Urethane Finish</i>
<i>Plank Size - ASTM F 2055</i>	<i>2mm (.80") x 7" x 48"</i>
<i>Total thickness - ASTM F 386</i>	<i>2mm</i>
<i>Material</i>	<i>100% Virgin Vinyl</i>
<i>Sq.ft. per Carton</i>	<i>46.72</i>
<i>Cartons Pallet / Pallet Cont.</i>	<i>50 / 20</i>
<i>Weight Carton</i>	<i>36 lbs.</i>

Project Plus Plank & Tile

<i>Warranty</i>	<i>Lifetime Residential & 10 year Light Commercial Limited Warranties</i>	
<i>Edge</i>	<i>Square Edge</i>	
<i>Recommended Adhesives</i>	<i>Mapei ECO399</i>	
<i>Material</i>	<i>100% Virgin Vinyl</i>	
<i>Tile Size</i>	<i>ASTM F 2055</i>	<i>184mmx 950mm, 7" x 48"</i>
<i>Classification</i>	<i>EN ISO 10582 ASTM F 1700</i>	<i>22+: Domestic General Class II Type A</i>
<i>Reaction to fire</i>	<i>EN13501-1 EN ISO 11925-2 EN ISO 9239-1</i>	<i>Bfi-S1 Pass Pass</i>
<i>Resistance to Chemicals</i>	<i>EN 423 ASTM F 925</i>	<i>Class O Pass</i>
<i>Resistance to Light</i>	<i>EN ISO 105-B02 ASTM F 1515</i>	<i>≥ 6 <8</i>
<i>Wear Resistance</i>	<i>EN 660-2 ASTM F 510</i>	<i>Wear Group : T</i>
<i>Dimensional stability</i>	<i>EN 434 ASTM F 2199</i>	<i>≤ 0.25% Pass</i>
<i>Acoustic Impact noise reduction</i>	<i>EN ISO 717-2 EN ISO 140-8</i>	<i>LW = 4 dB</i>
<i>Static electrical propensity</i>	<i>EN 1815</i>	<i>Voltage: 0.5kV</i>
<i>Residual Indentation</i>	<i>EN 433 ASTM F 1914</i>	<i>≤ 0.1mm <8%</i>
<i>Anti-slip property</i>	<i>DIN 51130</i>	<i>R10</i>
<i>VOC emission</i>	<i>ISO 16000</i>	<i>A+</i>
<i>Phthalates</i>	<i>EN 14372 CPSC -CH-C 1001-09.3</i>	<i>N.D. Pass</i>
<i>Castor chair continuous use</i>	<i>ISO 4918</i>	<i>Pass</i>
<i>Squareness</i>	<i>ASTM F 2055</i>	<i>Pass</i>
<i>Critical Radiant Flux</i>	<i>ASTM E648</i>	<i>Class 1</i>
<i>Smoke Density</i>	<i>ASTM E662</i>	<i>Pass</i>
	<i>Phthalate Free</i>	
	<i>Made in South Korea.</i>	